



# Motorola C290 Screen Replacement

Give a short summary.

Written By: Angelo Ballungay



## INTRODUCTION

This repair guide describes how to remove the screen of the Motorola C290.

---

### TOOLS:

- [Push Pin](#) (1)
  - [Spudger](#) (1)
  - [T6 Torx Screwdriver](#) (1)
  - [iFixit Opening Tools](#) (1)
-

## Step 1 — Outside Case removal



- Flip open your Motorola C290.
- Remove rubber stoppers located around main screen using a push pin.
- ⓘ This reveals four screws.
- Use a Torx T6 Screwdriver to unscrew the four screws.



## Step 2 — Removing the front casing



- Use a plastic opening tool to pry open a gap between the top cover and the face of the phone.
- Slide the plastic opening tool along gap and pry open case.
- Remove top cover.






### Step 3 — Disconnect the motherboard



- Unclip circuit attachments located on back of screen circuit board using a Spudger.

### Step 4 — Removing the motherboard/screen



- Insert the plastic opening tool between the metal screen components and the plastic frame at the corners.
- Firmly pry the screen components from the frame with a twisting motion
- ⚠ You will need to apply a good amount of force as you pry, twisting in a right-to-left motion.
- Completely remove screen components from frame.

To reassemble your device, follow these instructions in reverse order.

